



Lysy I Beams
ul.Tenczyńska 18, 32-067 Tenczynek
NIP: 5130279227
tel: +48 666 666 318
e-mail: lysyibeams@gmail.com

I-BEAMS : KROKWIE/DACHY 15°

MAKSYMALNA ROZPIĘTOŚĆ BELKI DLA 2 KLASY UŻYTKOWEJ L [m]
TABELA 1



BELKA 1 PRZĘSŁOWA 			
WARTOŚĆ OBCIĄŻENIA	STAŁE 0,90 [kN/m 2] ; OBCIĄŻENIE ŚNIEGIEM TERENU SK 0,90 [kN/m 2]		
TYP BELKI	ROZSTAW BELEK 0,30 [m]	ROZSTAW BELEK 0,40 [m]	ROZSTAW BELEK 0,60 [m]
I 150 45/45	3,53	3,17	2,71
I 200 45/45	4,58	4,12	3,54
I 220 45/45	4,97	4,47	3,85
I 240 45/45	5,34	4,81	4,14
I 250 45/45	5,53	4,98	4,29
I 300 45/45	6,41	5,78	4,99
I 350 45/45	7,25	6,54	5,65
I 360 45/45	7,41	6,69	5,77
I 400 45/45	8,05	7,27	6,28
I 450 45/45	8,82	7,96	6,88
I 500 45/45	9,56	8,64	7,47
I 150 45/70	4,08	3,65	3,11
I 200 45/70	5,29	4,76	4,08
I 220 45/70	5,75	5,17	4,43
I 240 45/70	6,18	5,56	4,78
I 250 45/70	6,40	5,76	4,95
I 300 45/70	7,42	6,69	5,75
I 350 45/70	8,39	7,56	6,52
I 360 45/70	8,58	7,73	6,66
I 400 45/70	9,31	8,40	7,24
I 450 45/70	10,20	9,20	7,94
I 500 45/70	11,05	9,97	8,61