



Lysy I Beams
ul.Tenczyńska 18, 32-067 Tenczynek
NIP: 5130279227
tel: +48 666 666 318
e-mail: lysyibeams@gmail.com

I-BEAMS : KROKWIE/DACHY 45°

MAKSYMALNA ROZPIĘTOŚĆ BELKI DLA 2 KLASY UŻYTKOWEJ L [m]
TABELA 3



BELKA 1 PRZĘSŁOWA 			
WARTOŚĆ OBCIĄŻENIA	STAŁE 0,90 [kN/m 2] ; OBCIĄŻENIE ŚNIEGIEM TERENU SK 0,90 [kN/m 2]		
TYP BELKI	ROZSTAW BELEK 0,30 [m]	ROZSTAW BELEK 0,40 [m]	ROZSTAW BELEK 0,60 [m]
I 150 45/45	4,44	4,00	3,45
I 200 45/45	5,73	5,18	4,47
I 220 45/45	6,21	5,61	4,85
I 240 45/45	6,68	6,04	5,22
I 250 45/45	6,91	6,24	5,40
I 300 45/45	8,00	7,24	6,27
I 350 45/45	9,04	8,18	7,09
I 360 45/45	9,24	8,36	7,25
I 400 45/45	10,03	9,08	7,87
I 450 45/45	10,98	9,94	8,62
I 500 45/45	11,91	10,78	9,35
I 150 45/70	5,14	4,63	3,98
I 200 45/70	6,65	6,00	5,17
I 220 45/70	7,21	6,51	5,62
I 240 45/70	7,75	7,00	6,04
I 250 45/70	8,01	7,24	6,25
I 300 45/70	9,29	8,39	7,26
I 350 45/70	10,48	9,48	8,20
I 360 45/70	10,72	9,69	8,39
I 400 45/70	11,63	10,51	9,11
I 450 45/70	12,72	11,51	9,97
I 500 45/70	13,78	12,47	10,81