



Lysy I Beams
ul.Tenczyńska 18, 32-067 Tenczynek
NIP: 5130279227
tel: +48 666 666 318
e-mail: lysyibeams@gmail.com

I-BEAMS : KROKWIE/DACHY 45°

MAKSYMALNA ROZPIĘTOŚĆ BELKI DLA 2 KLASY UŻYTKOWEJ L [m]
TABELA 6



BELKA 1 PRZĘSŁOWA 			
WARTOŚĆ OBCIĄŻENIA	STAŁE 1,20 [kN/m 2] ; OBCIĄŻENIE ŚNIEGIEM TERENU SK 0,90 [kN/m 2]		
TYP BELKI	ROZSTAW BELEK 0,30 [m]	ROZSTAW BELEK 0,40 [m]	ROZSTAW BELEK 0,60 [m]
I 150 45/45	4,09	3,69	3,17
I 200 45/45	5,29	4,77	4,11
I 220 45/45	5,73	5,17	4,47
I 240 45/45	6,16	5,57	4,81
I 250 45/45	6,37	5,76	4,97
I 300 45/45	7,39	6,68	5,78
I 350 45/45	8,35	7,55	6,53
I 360 45/45	8,54	7,72	6,68
I 400 45/45	9,27	8,38	7,26
I 450 45/45	10,15	9,18	7,95
I 500 45/45	11,00	9,95	8,63
I 150 45/70	4,73	4,26	3,65
I 200 45/70	6,13	5,52	4,75
I 220 45/70	6,65	5,99	5,16
I 240 45/70	7,15	6,45	5,56
I 250 45/70	7,39	6,67	5,75
I 300 45/70	8,57	7,74	6,68
I 350 45/70	9,68	8,74	7,56
I 360 45/70	9,89	8,94	7,72
I 400 45/70	10,74	9,70	8,39
I 450 45/70	11,75	10,62	9,19
I 500 45/70	12,73	11,51	9,96