



Lysy I Beams
ul.Tenczyńska 18, 32-067 Tenczynek
NIP: 5130279227
tel: +48 666 666 318
e-mail: lysyibeams@gmail.com

I-BEAMS : KROKWIE/DACHY 30°

MAKSYMALNA ROZPIĘTOŚĆ BELKI DLA 2 KLASY UŻYTKOWEJ L [m]
TABELA 8



BELKA 1 PRZĘSŁOWA 			
WARTOŚĆ OBCIĄŻENIA	STAŁE 1,45 [kN/m 2] ; OBCIĄŻENIE ŚNIEGIEM TERENU SK 0,90 [kN/m 2]		
TYP BELKI	ROZSTAW BELEK 0,30 [m]	ROZSTAW BELEK 0,40 [m]	ROZSTAW BELEK 0,60 [m]
I 150 45/45	3,33	2,99	2,55
I 200 45/45	4,32	3,89	3,33
I 220 45/45	4,69	4,22	3,62
I 240 45/45	5,05	4,55	3,91
I 250 45/45	5,22	4,70	4,04
I 300 45/45	6,06	5,46	4,70
I 350 45/45	6,86	6,18	5,33
I 360 45/45	7,01	6,32	5,45
I 400 45/45	7,61	6,87	5,93
I 450 45/45	8,34	7,53	6,50
I 500 45/45	9,05	8,17	7,06
I 150 45/70	3,84	3,44	2,92
I 200 45/70	5,00	4,49	3,83
I 220 45/70	5,43	4,87	4,17
I 240 45/70	5,84	5,25	4,50
I 250 45/70	6,04	5,43	4,66
I 300 45/70	7,02	6,31	5,42
I 350 45/70	7,93	7,15	6,14
I 360 45/70	8,11	7,31	6,28
I 400 45/70	8,81	7,94	6,83
I 450 45/70	9,64	8,70	7,49
I 500 45/70	10,45	9,43	8,13